



LC-XE10

3000 ANSI Lumens!

Get the crystal clear imaging of 3-panel LCD technology. Here's a bright, economical projector with auto just-about-everything.



- New! Auto Focus, Auto Keystone, Auto Set Up.
- New! Variable Audio Out. Corner Keystone Correction. USB Key Lock
- 3000 ANSI Lumens, 85% uniformity, and 450:1 contrast ratio.
- 3 panel LCD imaging delivers a rich, color saturated picture.
- True XGA resolution. SXGA, XGA, SVGA, and VGA compatible.
- Auto Lamp optimizes brightness. Fan noise only 34 dBA in Eco-Mode.
- Smart data compression / expansion, and video scaling.
- Power zoom and focus. Vertical & horizontal digital keystone correction.

- Wireless remote with mouse and Laser pointer. 7X digital zoom.
- Accepts Composite, S, and Component Video in all major standards.
- Displays both Regular 4:3 and Widescreen 16:9 ratio video formats.
- Optionally converts SDi to SDp. Supports HDTV 720p, 1035i, and 1080i.
- Variable Power Management option. Optional local or remote keylock.
- DVI is HDCP compatible. Slideshow Page Up/Down on remote control.
- Remote Pointer/Spotlight effect. Custom warm-up screen image option.
- 3 Year* Projector Warranty!

EIKI
PROJECTORS

EIKI Means Projectors ... and more!

LC-XE10



CAUTION
LASER RADIATION
DO NOT STARE INTO BEAM
MAX OUTPUT: 10mW
WAVELENGTH: 650-20nm
CLASS II LASER PRODUCT

Hg
Lamp Contains Mercury. Do not put in trash.
Dispose-of-as Hazardous Waste, according to
Local, State or Federal Laws.

INCLUDED ACCESSORIES:

Owner's Manual. AC Power Cord. Lens Cover. VGA-type Computer Input Cable (DVI-I ~ HD15). Wireless Remote Control With Mouse and Laser Pointer & Batteries (AA x 2). Mouse cable for computer USB Port. Dust Cover.

OPTIONAL ACCESSORIES:

Optional Accessories: Replacement Lamp. USB Security Key. MAC Adapter. MAC Monitor Cable. 9 Pin Serial cable for RS-232 communications. Executive Carry Case with Computer Compartment. Luggage-Style ("wheeler") Carrying Case with Wheels, Telescoping Handle, and Detachable Computer Compartment. ATA-Style Shipping Case with Wheels and Telescoping Handle. Ceiling Mount. Ceiling Post and Plate. 33' (10m) Extension Cable for Serial Cable. Multi Card Director system supports 1. Computerless Slide Show System, 2. Wired Network Projector Control, 3. Wi-Fi Content Delivery and Projector Control System. EZtrol Local Control. NPC-1 Network Control.

LC-SE10

Here's auto just-about-everything at lower cost SVGA resolution. Get all the same features and specifications as the LC-XE10, except :
Contrast Ratio: 500:1 (Full ON/OFF). Horizontal Resolution: 700 TV Lines. Screen Pixels: 800x600 in stripe configuration. Total Pixels: 440,000 ((800x600) x 3). Scanning Frequency: Auto: H Sync. 15-80 kHz; V Sync. 50-100Hz. Dot Clock: 100 MHz. Computer Native resolution: 800x600 (SVGA). Computer Compatibility: XGA, SVGA, VGA. Computer Formats: 1024x768, 800x600, 640x480.

SPECIFICATIONS: LC-XE10

Screen Brightness	3000 ANSI Lumens / 2250 in Eco-Mode
Illumination Uniformity	85%+
Size of Color Palette	16.7 Million
Contrast Ratio	450:1 (Full ON/OFF)
Horizontal Resolution	800 TV Lines
Projection Lamp	300 Watt NSH (240 Watt in Eco mode)
Estimated Lamp Life	2,000 Hours
Imaging System	0.99" PolySilicon active matrix TFT Panels x 3
Screen Pixels	1024 x 768 in stripe configuration
Total Pixels	2,359,296 ((1024 x 768) x 3)
Lens Type	Power Zoom and Focus
Lens Specs	Speed: f:1.7~2.1; FL: 1.32~1.70 in. (33.6~43.2 mm)
Lens Ratios	Zoom Max:Min: 1.29:1; Throw:Width: 1.67~2.15:1
Image Diagonal	31~300 in. (78.7~762 cm)
Image Width	2.1~20 ft. (0.6~6.1 m.)
Throw Distance	4.3~33.1 ft. (1.3~10.1 m.)
Front Elevation/Maximum Tilt	up to 10.3° up / +/- 20°
Anti Keystone	Fixed Image Offset, Ratio (Top:Bottom) 9:1
Vertical Keystone Correction	Digital, up to 40° up or down
Horizontal Keystone Correction	Digital: up to 20° left or right
Corner Keystone Correction	Present
Scanning Frequency	Auto: H Sync. 15-100kHz; V Sync. 50-100Hz
Dot Clock	140 MHz
Image Orientation	Normal, Reversed, Inverted
Local Control/Power Management	Full Function/Auto Shut-Off
Remote Projector & Mouse Control	Wireless (Infra Red) with Laser Pointer x 1
Mouse Port	USB x 1
Service Port (RS-232)	Mini DIN 8 Pin x 1
Computer Native Resolution	1024 x 768 (XGA)
Computer: Compatibility	SXGA, XGA, SVGA, VGA, MAC
Computer: Formats	1400 x 1050 ~ 640 x 480
Computer: Higher Resolutions	Displayed panned or Smart Compressed
Computer: Lower Resolutions	Displayed normal or Smart Expanded
Computer: Channels	2
Computer: Input 1	DVI-I x 1 (HD15 via Supplied Input Cable)
Input 2 / Monitor Out	HD15 x 1
Computer: Audio In 1 & 2	Stereo: MiniStereo x 2
Video Compatibility	NTSC/PAL/SECAM/NTSC 4.43/PAL-M&N
Video: Formats Supported	Normal 4:3 and Wide Screen 16:9
Video: Image Sizing	Video Scaling Technology
Video: Channels	1
Video: In RCA x 3 (Composite/Component: Y,Pb/Cb,Pr/Cr)	S-Video x 1
Video: Audio: Input	RCA x 2 (L&R)
Audio: Amplifier	Mono: 1 Watts RMS
Audio: Built In Speakers	1.1 in. (28 mm) x 1
Audio: Output - Variable Audio	Out Stereo: MiniStereo x 1
Fan Noise	38 dBA / 34 dBA in Eco-Mode
Cabinet Size** (HxWxD)	4.4 x 15.35 x 10.91 in. (112 x 390 x 277 mm.)
	** excluding raised portions
Weight	12.8 lbs. (5.8 kg)
Packaged Size (H x W x D)	13.3 x 24.7 x 18.0 in. (337 x 626 x 456 mm)
Packaged Weight	21.2 lb (9.6 kg)
Power Requirements	100-240V AC, 50/60Hz
Power Consumption / Heat: Normal	400 W / 1365 BTU/hr. (344 Kcal/hr.)
Power Consumption / Heat: Eco	320 W / 1092 BTU/hr. (275 Kcal/hr.)
Power Cord	10' (3M) Type 3, Detachable
Safety Compliance	UL Listed
Security Facilities	Kensington® Security Slot; USB Key Lock
Operating Temperature	41~95°F (5~35°C)
User Maintenance	Clean Air Filter, Replace Lamp
Warranty: Projector	3 Yr. / 6000 Hr. *(Parts/Labor to Correct Defects)
Warranty: Lamp	90 Days (Failed Lamp Replaced Pro-Rata)
	* whichever occurs first

Talk to your EIKI Dealer... the "pro" in projection.



Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130
Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com
In Canada, 310 First St.-Unit 2, P.O. Box 156, Midland, ON L4R 4K8
Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com
Fax-on-Demand: (Toll Free) 877-345-4329 <http://www.eiki.com>

Specifications subject to change without notice.

©2003 EIKI International, Inc. Printed in the USA. 12/01/03